

# One Touch Pneumatics

## Fitting and Tubing Specialists

### DOT DIN 74324-1 NYLON TUBING

- 100% Pressure Tested
- Abrasion Resistant
- Use with Compression or Push to Connect Fittings
- Excellent UV Stability
- Kink Resistant
- Standard Colors

**Typical Application:** Air brake line for Trucks, Buses, Heavy Vehicles, and Cars

Part Number	Nominal Size	Tube O.D.	Outside Diameter	Inside Diameter	Nominal Wall Thickness	Available Working Pressure at 73°F/23°	Minimum Bend Radius r <sup>1</sup>	Standard Reel
			mm	mm	mm	psi / bar	mm	feet / meter
1011-04-XX-1000	4x1	4.0	4	2	0.9	653 / 45	20	1000 / 305
1011-06-XX-1000	6x1	6.0	6	4	0.9	392 / 27	30	1000 / 305
1011-08-XX-1000	8x1	8.0	8	6	0.9	276 / 19	40	1000 / 305
1011-09-XX-1000	9x1.5	9.0	9	6	1.35	392 / 27	45	1000 / 305
1011-10-XX-1000	10x1	10.0	10	8	0.9	218 / 15	60	500 / 152
1011-10-A-XX-1000	10x1.25	10.0	10	7.5	1.12	276 / 19	60	500 / 152
1011-11-XX-1000	11x1.5	11.0	11	9	1.35	305 / 21	60	500 / 152
1011-12-XX-1000	12x1.5	12.0	12	8	1.35	276 / 19	60	250 / 76
1011-14-XX-1000	14x2	14.0	14	10	1.80	319 / 22	75	250 / 76
1011-15-XX-1000	15x1.5	15.0	15	12	1.35	218 / 15	90	250 / 76
1011-16-XX-1000	16x2	16.0	16	12	1.80	276 / 19	95	250 / 76
1011-18-XX-1000	18x2	18.0	18	14	1.80	247 / 17	100	250 / 76

XX represents color code

\* Notes stocked sizes

BLACK is stocked color. Also Available in: GREEN / YELLOW / RED / BLUE

#### Construction Material:

Single wall extruded Nylon (polyamide)

#### Operating Parameters:

Temperatures Range:

-40°F to +200°F (-40°C to +93°C)

#### Certifications:

Meets DIN Specification 74324-1 & 73378



[www.onetouchpneumatics.com](http://www.onetouchpneumatics.com)